

Titan Energetics Division Introduces

Outlaw™

Good Hole

Larger Entrance Hole and Deeper Penetration



Gun Systems	Part #	Hole Diameter	Penetration
2" 4/6 SPF	RTG-2106-331 API RP-43 Performance in 2-7/8" Casing ; 5,720 psi Target	0.36" (9.14 mm)	11.82" (300.23 mm)
3-1/8" 4/6 SPF	EXP-3319-331 API RP-43 Performance in 4-1/2" Casing; 6,710 psi Target	0.49" (12.45 mm)	21.92" (556.8 mm)
3-3/8" 4/6 SPF	EXP-3323-331 API RP-43 Performance in 4-1/2" Casing; 6,660 psi Target	0.54" (13.72 mm)	20.61" (523.5 mm)
	EXP3325-331 API RP-43 Performance in 4-1/2" Casing; 5,890 psi Target	0.57" (14.48 mm)	29.81" (757.17 mm)
4" 4/6 SPF	EXP-3323-331 API RP-43 Performance in 5-1/2" Casing; 5,870 psi Target	0.49" (12.45 mm)	30.97" (786.64 mm)
	EXP-3325-331 API RP-43 Performance in 5-1/2" Casing; 6,045 psi Target	0.56" (14.22 mm)	35.61" (904.5 mm)
7" 12 SPF	EXP-7039-331 API RP-43 Performance in 9-5/8" Casing; 5,345 psi Target	0.75" (19.05 mm)	28.54" (724.9 mm)
	EXP-7039-332 API RP-43 Performance in 9-5/8" Casing; 5,345 psi Target	0.78" (19.812mm)	24.51" (622.554 mm)

Contact your local Titan supplier for complete specifications and charge compatibility.



TITAN SPECIALTIES, LTD.
Sales 800-692-4486

TITAN ENERGETICS DIVISION
Sales 800-320-5110

TITAN INSTRUMENT DIVISION
Sales 800-692-4486

TITAN PERFORATING DIVISION
Sales 800-692-4486

Your Worldwide
Solution