



SPECIFICATIONS

<p><u>MODEL NUMBER</u> <i>as shown (2.25" wheels)</i></p> <p>1200-168-225-1 *</p>
<p><u>MAX TEMPERATURE RATING</u></p> <p>400° F (204.4° C)</p>
<p><u>PRESSURE RATING</u></p> <p>15,000 PSI (103 MPa)</p>
<p><u>MAKE UP LENGTH</u></p> <p>15.50" (39.37 cm)</p>
<p><u>WEIGHT</u></p> <p>9 lbs (4.1 kg)</p>
<p><u>MAX DIAMETER</u></p> <p>Varies with wheel size</p> <p>Min: 1.75" (4.45 cm) Max: 2.25" (5.72 cm)</p>
<p><u>OPTIONS</u></p> <p>* Other wheel sizes available</p>

TOTAL LENGTH
15.50 in [39.37 cm]



**1 11/16
INCH
(4.29 CM)**

**ROLLER
ASSEMBLY**

999B16A0 Apr-05



SPECIFICATIONS

MODEL NUMBER
as shown (3.25" wheels)

1200-200-325-1 *

MAX TEMPERATURE RATING

400° F (204.4° C)

PRESSURE RATING

15,000 PSI (103 MPa)

MAKE UP LENGTH

22.50" (57.15 cm)

WEIGHT

20 lbs (9.1 kg)

MAX DIAMETER

Varies with wheel size

Min: 2.125" (5.40 cm)

Max: 3.25" (8.26 cm)

OPTIONS

*** Other wheel sizes available**

TOTAL LENGTH
22.50 in [57.15 cm]



**2
INCH
(5.08 CM)**

**ROLLER
ASSEMBLY**

999B20A0 Apr-05